

5. SUMMARY, CONCLUSIONS, IMPLICATIONS AND FUTURE RESEARCH NEEDS

5.1 Summary

Soil morphologic and physical properties were studied on three suburban and two rural sites dominated by Cecil (Typic Hapludult, clayey, kaolinitic, thermic) soils to investigate the role of suburban soil surfaces in infiltration and stormwater runoff. Significant proportions of the suburban sites (44.6 to 67.3%) were composed of disturbed soil profiles. Some soils had been excessively disturbed, thus often taxonomically yielding a new soil.

The suburban landscape is dominated by soil surfaces. Soil surfaces comprised 58.1 to 72.9% of the suburban sites studied, while impervious surfaces accounted for 27.1 to 39.1%. County soil surveys of metropolitan areas by the National Cooperative Soil Survey do not provide a sagacious assessment of the soils, nor the relative percent of impervious cover. The "urban complex" mapping units of the National Cooperative Soil Survey provides limited useful information for urban watershed planning and engineering. The nature and extent of excessively disturbed urban soils is normally not included in county soil surveys.

Typic Hapludult soil series are probably too broadly defined to allow for meaningful soil classification for urban purposes. Fine and very fine (clayey) family soil texture criteria should be established in the Ultisol order. Innovative use of soil phases can provide for more meaningful urban soil maps. Mapping, classification and characterization of disturbed urban soils is necessary for accurate assessments of suburban watershed hydrology.

Laboratory soil-water data were determined for 365 undisturbed soil cores. The volume of macroporosity (60-cm^{-1} tension) is closely

correlated to the saturated hydraulic conductivity of the soil cores. Disturbed soil profiles had greater bulk densities, lower volume of macroporosity and slower saturated hydraulic conductivities than undisturbed soil profiles. These trends were most notable in subsoil core samples.

Soil-water characteristics of disturbed soil profiles were significantly different from undisturbed soil profiles. Data for the Sudbury Suburban Watershed indicate that the volume of macropores in subsoils of disturbed sites was 15.7 to 72.3% of that for forested sites, while the saturated hydraulic conductivity was 0.5 to 24.2% of that for forest subsoils. The conversion of forest to suburban soil conditions produces a markedly different soil-water environment. The saturated hydraulic conductivity of disturbed subsoils on the Mine Valley Subdivision was 7.9 to 41.1% of that of forest subsoils. The saturated hydraulic conductivity of disturbed subsoils on the Meredith Townes Subdivision was 11.7 to 15.7% of that of forest subsoils.

The laboratory soil-water physical data for the Schenck Pasture and Schenck Forest watersheds illustrate highly structured porous soils that have mean saturated hydraulic conductivities in the subsoil of greater than 5 cm/hour.

The macro and micromorphology of selected soils were studied to evaluate the soil pore system. The extent of tubular transpedal pore development in the argillic horizon strongly governs the soil-water and infiltration characteristics of the profiles. Tubular transpedal pores were generally well developed in forest soil profiles, but were lacking in samples studied from old cultivated fields with dense plow pans and disturbed suburban subsoils. Man-made disturbance of argillic horizons

can produce significant alteration to the soil fabric producing a collapse and filling most notably of the larger pores and, or blockage of their continuity.

Man-made disruption, transport and deposition of clayey soil material produces a resultant soil with distinctive micromorphological characteristics. Pedorelicts and remnants of diagnostic argillic horizons were commonly found in the "man-made" soils studied. Both the cutting and filling of soil material create distinct macro and micro-morphologic characteristics in the resultant soils, that can serve as diagnostic criteria in the recognition and classification of these soils. Loamy and clayey "man-made" fill soils were found to invariably contain remnants of argillic diagnostic horizons. These soils would normally be classified as Arents.

Man-made cutting into an argillic horizon was found to produce a resultant soil with a thin fill or mixed layer with pedorelicts or remnants of the argillic horizon over the remainder of the previous profile. Depending upon the amount of or lack of a remaining argillic horizon, these soils would normally be classified as Typic Hapludults (>25 cm of argillic), Ochreptic Hapludults (<25 cm of argillic) or Typic Udorthents (no argillic).

Double-ring constant head flooding infiltrometers were used to conduct 136 infiltration tests on various soil conditions (land types) on the five research sites. Infiltration tests were made under both moist and wet antecedent soil moisture conditions. Suburban infiltration curves had such an early and sharp transition from the early falling limb to the slower constant rate of decline or steady state rate, that it was necessary to make semi-log plots of the curves. The

transition to a steady state rate or a slow constant rate of decline generally occurred within 5 minutes for wet antecedent suburban soil conditions.

Significant differences occurred among the final constant infiltration rates. Land types that consisted of disturbed soil profiles had significantly lower infiltration rates than land types of undisturbed soils. Final constant infiltration rates of excessively disturbed soils of the Sudbury Suburban Watershed were 1 to 5% of those of forest soil profiles, and 3 to 16% of those for the least disturbed urban soil profiles. Significantly lower final constant infiltration rates were measured for disturbed soil profiles (cut and fill land types) than undisturbed soil profiles on all sites. The mean final constant infiltration rates for Schenck Forest and Schenck Pasture Watersheds were sufficiently high (>8 cm/hour) to only rarely produce appreciable runoff.

The final constant infiltration rates measured for the various soils do not agree with USDA soil hydrologic groups. Cecil Series soils are rated by the USDA to have a final constant infiltration rate of 0.38 to 0.76 cm/hour. Essentially the only measured final constant infiltration rates less than 1.00 cm/hour occurred for disturbed soil conditions. Forest, pasture and relatively undisturbed suburban soils generally had final constant infiltration rates significantly greater than 1.00 cm/hour.

Estimates of percent runoff from the various soil surfaces were calculated from wet antecedent infiltration data with an infiltration excess method. Estimated percent of runoff for short duration rainstorms was found not to agree with traditional runoff coefficients used in the rational method of runoff estimation.

Infiltration rates were compared to rainfall-runoff records for the Sudbury Suburban, Schenck Pasture and Schenck Forest Watersheds. Total runoff for short duration convective rainstorms varied between 17.5 and 80.4% for Sudbury Suburban Watershed, 0.1 and 24.6% for Schenck Pasture Watershed and 0.7 and 21.5% for Schenck Forest Watershed. Percent total runoff was most sensitive to 1-day antecedent rainfall ($r^2 = 0.931$) for Sudbury Suburban Watershed. While, percent total runoff was most sensitive to 5-day antecedent rainfall ($r^2 = 0.691$) for Schenck Forest Watershed and to 10-day antecedent rainfall ($r^2 = 0.560$) for Schenck Pasture Watershed.

Estimates of direct runoff were calculated from infiltration data with an infiltration excess method for the Sudbury Suburban Watershed. Estimates of direct runoff for three rainfall-runoff events were found to closely agree with the actual direct runoff by hydrograph separation. Runoff from soil surfaces was estimated to represent 40 to 50% of the direct runoff for the most severe rainstorm events on record for the Sudbury Suburban Watershed. Runoff from soil surfaces appears to sufficiently coincide in space and time with runoff from impervious surfaces to produce the record flooding. Runoff from excessively disturbed soils appears to be an important to dominant factor in the generation of mean maximum annual and larger floods.

5.2 Conclusions

Suburban soils and soil conditions were found to be substantially different than that for analogous undisturbed soils. Suburban and urban soils have been sufficiently disturbed to create significantly different soil-water environments than for undisturbed soils.

The soil conditions on suburban Piedmont watersheds greatly affect the watershed hydrology. Infiltration rates for suburban disturbed soils can have one to two orders of magnitude lower final constant rates. Although suburban infiltration rates are extremely heterogeneous, they appear to correlate with recognizable land types occurring across the suburban landscape. Significant soil disturbance appears to occur on a minority of suburban soil surfaces, but is a major factor in the generation of stormwater runoff.

Use of the USDA soil hydrologic group rating for the Cecil series is inappropriate for suburban conditions. USDA soil hydrologic groups consistently under-estimated the final constant infiltration rates for undisturbed forest, pasture and suburban soils that were studied.

Runoff from disturbed soils appears to sufficiently coincide in time and space with runoff from impervious surfaces to contribute to the peak of the flood hydrograph. The antecedent rainfall dramatically governs runoff production from the soil surfaces. Critical stormwater runoff discharges appear to only occur with 1 to 2-day wet antecedent rainfall conditions. An average infiltration value for a suburban watershed does not reflect the soil variability and thus does not provide for the multiplicity of infiltration and runoff rates. Suburban soil runoff appears to occur primarily from partial source areas consisting of disturbed soils. Reasonably accurate metropolitan stormwater modelling for the Piedmont region requires deterministic soil hydrologic evaluations rather than use of USDA soil hydrologic groups and more detailed soil maps than county soil surveys.

Metropolitan stormwater modelling can be improved by the accurate use of soil-water and infiltration data. Accurate soil hydrologic data

should be obtained for the major soils and soil conditions in the urban area. Soil hydrologic data should be carefully scrutinized with detailed rainfall-runoff records for locally monitored small suburban and urban watersheds.

The use of the various infiltration equations will not necessarily improve runoff prediction without the proper selection or estimate of final constant infiltration rates which are so all determining. Infiltration equations, e.g., Horton's equation, with a negative exponent should produce the best results, because a more rapid decay to the final constant infiltration rate can be achieved.

The amount of impervious surfaces, disturbed soil surfaces and relatively undisturbed soil surfaces should be determined or estimated for the watershed in question. Final constant infiltration rates should be determined or estimated for various soil conditions; at least disturbed and undisturbed soil surfaces. Runoff should be modelled for impervious, disturbed soil surfaces and undisturbed soil surfaces separately. This can be theoretically accomplished by modelling these three areas as separate flows, i.e., partial source areas, until they reach a common conduit or channel. The timing of these flows is critical; therefore, averages of distinctly different final constant values should not be made. The time of travel of soil-generated runoff must be considered in reference to the average distance before runoff waters are intercepted by impervious surfaces or conduits.

5.3 Implications and Future Research Needs

One of the most disturbing general conclusions that can be drawn from this research is that most currently available soils data and

techniques for estimating suburban infiltration and runoff are inappropriate. This might be expected since there has been a virtual lack of soil hydrologic research in urban areas. Hopefully, the findings in this research effort will (1) provide a more precise understanding of the problem(s), (2) provide useful typical soil-water data of clayey kaolinitic Piedmont suburban soils and (3) stimulate academic and professional interest in suburban soil and hydrologic studies.

The focus of this research was aimed at developing a more precise understanding of suburban soils and their influence on watershed hydrology. The research findings tend to disagree with many perceptions and professional practices in current use. The lack of agreement between the author's data and the USDA soil hydrologic group ratings suggests that fundamental problems exist in runoff estimation.

The practice of runoff estimation needs to be more closely related to actual discharge data from small suburban watersheds. The largest source of such data which is available for the North Carolina Piedmont was collected by the USCS for Putnam's (1972) study. Further analysis and study of Putnam's rainfall-runoff data is recommended. Correlations between the rainfall-runoff data and antecedent rainfall, soils and watershed conditions should be investigated.

Control of the rate and velocity of stormwater runoff in suburban areas can theoretically be accomplished by reducing the volume of runoff production. Increased detention of rainfall in suburban soils will necessitate improved soil and agronomic management. Research will be necessary to determine effective and efficient soil and agronomic techniques. The effectiveness of soil management techniques should be evaluated from hydrologic measurement of watershed experimentation.

Suburban soil hydrologic management may provide one of the more reasonable means of reducing stormwater runoff, controlling downstream stream-bank degradation, reducing urban soil erosion and improving water quality.

Minimizing soil disturbance during urbanization will reduce runoff production. Although runoff reduction can be accomplished by lower development densities, this practice only redistributes rather than solves the problem. Fundamental changes to reduce the volume of runoff can occur by (1) planning suburban development to more closely fit the natural terrain, *i.e.*, reducing cutting and filling; (2) increasing common open space by clustering development; (3) transferring stormwater runoff from impervious surfaces onto adjacent open space and (4) reducing the amount of impervious surfaces.

6. LIST OF REFERENCES

- Ahuja, L. B., S. A. El-Swaify and A. Rahman. 1976. Measuring hydrologic properties of soil with a double-ring infiltrometer and multiple-depth tensiometers. *Soil Sci. Soc. Amer. Proc.* 40(4):494-499.
- Anderson, D. G. 1970. Effects of urban development on floods in northern Virginia. U.S. Geological Survey Water-Supply Paper 2001-C, U.S.G.P.O., Washington, DC. 22 pp.
- Atkinson, B. W. 1971. The effect of an urban area on the precipitation from a morning thunderstorm. *Journ. Applied Meteor.* 10:47-55.
- Baver, L. D. 1936. Soil characteristics influencing the movement and balance of soil moisture. *Soil Sci. Soc. Amer. Proc.* 1:431-437.
- Beasley, R. S. 1976. Contribution of subsurface flow from the upper slopes of forested watersheds to channel flow. *Soil Sci. Soc. Amer. Journ.* 40(6):955-957.
- Beckmann, G. G. and K. J. Smith. 1974. Micromorphological changes in surface soils following wetting, drying and trampling, pp. 832-845. In G. K. Rutherford (ed.), *Soil Microscopy*. Proc. 4th Int. Working Meeting on Soil Micromorphology. Limestone Press, Kingston, Ontario, Canada.
- Bertoni, J., W. E. Larson and W. D. Shrader. 1958. Determination of infiltration rates on Marshall silt loam from runoff and rainfall records. *Soil Sci. Soc. Amer. Proc.* 22(6):571-574.
- Betson, R. P. 1964. What is watershed runoff? *Journ. Geophysical Research* 69(8):1541-1552.
- Bouma, J. and J. C. Anderson. 1973. Relationships between soil structure characteristics and hydraulic conductivity, pp. 77-105. In R. R. Bruce, K. W. Flach and H. M. Taylor (eds.), *Field Soil Water Regime*. Spec. Publ. Series No. 5, Soil Sci. Soc. Amer., Inc., Madison, WI.
- Bouma, J. and F. D. Hole. 1965. Soil peels and a method for estimating biopore size distribution in soil. *Soil Sci. Soc. Amer. Proc.* 29(4):483-485.
- Bouma, J. and F. D. Hole. 1971. Soil morphology and hydraulic conductivity of adjacent virgin and cultivated pedons at two sites: A Typic Argiudoll (silt loam) and a Typic Eutrochrept (clay). *Soil Sci. Soc. Amer. Proc.* 35(2):316-319.
- Brewer, R. 1976. *Fabric and Mineral Analysis of Soils*. John Wiley and Sons, Inc., New York. 482 pp.

- Bruce, R. R., A. W. Thomas and F. D. Whisler. 1976. Prediction of infiltration into layered field soils in relation to profile characteristics. *Trans. Amer. Soc. Agri. Engin.* 19(4):693-698, 703.
- Bruce, R. R. and F. D. Whisler. 1973. Infiltration of water into layered field soils, pp. 77-89. *In* A. Hadas *et al.* (eds.), *Physical Aspects of Soil Water and Salts in Ecosystems*. Springer-Verlag, New York.
- Brunauer, S., P. H. Emmett and E. Teller. 1938. Absorption of gases in multimolecular layers. *Journ. Amer. Chem. Soc.* 60(2):309-319.
- Buol, S. W. and D. M. Fadness. 1961. A new method of impregnating fragile materials for thin sectioning. *Soil Sci. Soc. Amer. Proc.* 25(3):253.
- Buol, S. W. and F. D. Hole. 1959. Some characteristics of clay skins on peds in the B horizon of a gray-brown Podzolic soil. *Soil Sci. Soc. Amer. Proc.* 23(3):239-241.
- Buol, S. W. and F. D. Hole. 1961. Clay skin genesis in Wisconsin soils. *Soil Sci. Soc. Amer. Proc.* 25(5):377-379.
- Canfield, N. L. and C. A. Woollum. 1968. Washington metropolitan area precipitation and temperature patterns. *Tech. Memo. WBTM-ER-28, Nat. Oceanic and Atmospheric Admin., Asheville, NC.* 32 pp.
- Carter, D. L., M. D. Heilman and C. L. Gonzalez. 1965. Ethylene glycol monoethyl ether for determining surface area of silicate minerals. *Soil Sci.* 100(5):356-360.
- Carter, R. W. 1961. Magnitude and frequency of floods in suburban areas, pp. B9-B11. *Short papers in the geologic and hydrologic sciences. Prof. Paper 424-B, U.S. Geological Survey, U.S.G.P.O., Washington, DC.*
- Carvallo, H. O., D. K. Cassel, J. Hammond and A. Bauer. 1976. Spatial variability of *in situ* unsaturated hydraulic conductivity of Maddock sandy loam. *Soil Sci.* 121(1):1-8.
- Changnon, S. A., Jr. 1968. The LaPorte weather anomaly--Fact or fiction? *Bull. Amer. Meteor. Soc.* 49(1):4-11.
- Changnon, S. A., Jr. and F. A. Huff. 1973. Precipitation modification by major urban areas. *Bull. Amer. Meteor. Soc.* 54(12):1220-1232.
- Chapman, S. L. and M. L. Jackson. 1969. Quantitative clay mineralogy of selected soils from north central United States, p. 131. *Agron. Abstracts, 1969 Annual Meetings, Amer. Soc. Agron., Madison, WI.*

- Childs, E. C. 1969. An Introduction to the Physical Basis of Soil Water Phenomena. John Wiley and Sons, London, England. 493 pp.
- Chow, V. T. (ed.). 1964. Handbook of Applied Hydrology. A Compendium of Water-Resources Technology. McGraw-Hill, Inc., New York. 1646 pp.
- Clawson, M. 1971. Suburban Land Conversion in the United States: An Economic and Governmental Process. Johns Hopkins Press, Baltimore, MD. 406 pp.
- Clifford, W. B. 1977. Recent population trends in North Carolina and the southern region: 1970-1975. Report No. 64, Dept. of Sociology and Anthropology, NCSU, Raleigh. 18 pp.
- Costa, J. E. 1974. Response and recovery of a Piedmont watershed from tropical storm Agnes, June 1972. Water Resour. Res. 10(1):106-112.
- Day, P. R. 1965. Particle fractionation and particle-size analysis, pp. 545-567. In C. A. Black (ed.), Methods of Soil Analysis. Agronomy Series No. 9. Soil Sci. Soc. Amer., Madison, WI.
- DeAngelis, R. M. and W. T. Hodges. 1972. Preliminary climatic data report hurricane Agnes, June 14-23, 1972. Tech. Memo., EDS NCC-1, Nat. Oceanic and Atmospheric Admin., Asheville, NC. 62 pp.
- Dixon, J. B. 1965. Quantitative analysis of kaolinite and gibbsite in soils by differential thermal and selective dissolution methods, pp. 83-89. Clays and Clay Minerals, Proc. 14th Conf. Pergamon Press, London, England.
- Dixon, R. M. 1966. Water infiltration responses to soil management practices. Unpublished Ph.D. thesis, Dept. of Soil Science, Univ. Wisconsin, Madison. Univ. Microfilms Int., Ann Arbor, MI.
- Dixon, R. M. and A. E. Peterson. 1971. Water infiltration control: A channel system concept. Soil Sci. Soc. Amer. Proc. 35(6):968-973.
- Dreibelbis, F. R. and F. A. Post. 1940. Studies on soil moisture relationships at the North Appalachian Experimental Watershed. Soil Sci. Soc. Amer. Proc. 5:377-385.
- Dreibelbis, F. R. and F. A. Post. 1943. Some seasonal changes in the pore space and moisture relationships of woodland, pasture, and cultivated soils. Soil Sci. Soc. Amer. Proc. 8:102-108.
- Dunne, T. and R. D. Black. 1970a. An experimental investigation of runoff production in permeable soils. Water Resour. Res. 6(2): 478-490.
- Dunne, T. and R. D. Black. 1970b. Partial area contributions to storm runoff in a small New England watershed. Water Resour. Res. 6(5): 1296-1311.

- Dunne, I., T. R. Moore and C. H. Taylor. 1975. Recognition and prediction of runoff-producing zones in humid regions. *Hydrol. Sci. Bull.* 20(3):305-327.
- Espey, W. H., C. W. Morgan and F. D. Masch. 1966. Study of some effects of urbanization on storm runoff from a small watershed. Report No. 23, Texas Water Development Board, Austin, TX. 109 pp.
- Felton, P. M. and H. W. Lull. 1963. Suburban hydrology can improve watershed conditions. *Public Works* 94(1):93-94.
- Fox, H. L. 1976. The urbanizing river: A case study in the Maryland Piedmont, pp. 245-272. *In* D. R. Coates (ed.), *Geomorphology and Engineering*. Dowden, Hutchinson and Ross, Stroudsburg, PA.
- Free, G. R., G. M. Browning and G. W. Musgrave. 1940. Relative infiltration and related physical characteristics of certain soils. *Agri. Dept. Tech. Bull.* 729, U.S.G.P.O., Washington, DC. 52 pp.
- Goddard, J. E. 1973. An evaluation of urban flood plains. *Tech. Memo. No. 19*, Amer. Soc. Civil Engin., Urban Resour. Res. Prog., New York. 40 pp.
- Graf, W. L. 1976. The impact of suburbanization on fluvial geomorphology. *Water Resour. Res.* 11(5):690-692.
- Green, R. E. and J. C. Corey. 1971. Calculation of hydraulic conductivity: A further evaluation of some predictive methods. *Soil Sci. Soc. Amer. Proc.* 35(1):3-8.
- Gupta, A. and H. L. Fox. 1974. Effects of high magnitude floods on channel form: A case study in the Maryland Piedmont. *Water Resour. Res.* 10(3):499-503.
- Hammer, T. R. 1971. Effects of urbanization on stream channels and stream flow. *Regional Sci. Res. Instit.*, Philadelphia, PA. 272 pp.
- Hammer, T. R. 1972. Stream channel enlargement due to urbanization. *Water Resour. Res.* 8(6):1530-1537.
- Hardy, A. V., C. B. Carney and H. V. Marshall, Jr. 1967. Climate of North Carolina research stations. *Bull. No. 433*, Agri. Experiment Sta., NCSU, Raleigh. 75 pp.
- Harnack, R. P. and H. E. Landsberg. 1975. Selected cases of convective precipitation by the metropolitan area of Washington, D.C. *Journ. Applied Meteor.* 14(6):1050-1060.
- Heilman, M. D., D. L. Carter and C. L. Gonzalez. 1965. The ethylene glycol monoethyl ether (EGME) technique for determining soil surface area. *Soil Sci.* 100(6):409-413.

- Hewlett, J. D. 1961. Soil moisture as a source of baseflow from steep mountain watersheds. Paper No. 132, Southeastern Forest Experiment Station, U.S. Forest Service, Washington, DC. 11 pp.
- Hewlett, J. D., J. C. Fortson and G. B. Cunningham. 1977. The effect of rainfall intensity on storm flow and peak discharge from forest land. *Water Resour. Res.* 13(2):259-266.
- Hewlett, J. D. and A. R. Hibbert. 1967. Factors affecting the response of small watersheds to precipitation in humid areas, pp. 275-290. In W. E. Sopper and H. W. Lull (eds.), *International Symposium on Forest Hydrology*. Pergamon Press, Oxford, England.
- Hewlett, J. D. and W. L. Nutter. 1970. The varying source area of streamflow from upland basins, pp. 65-83. *Proc. of Symposium on Interdisciplinary Aspects of Watershed Management*. Amer. Soc. Civil Engin., New York.
- Hillel, D. 1971. *Soil and Water, Physical Principles and Processes*. Academic Press, New York. 288 pp.
- Holtan, H. N. 1958. Infiltration estimates based on vegetation and the soil profile. *Amer. Soc. Agri. Engin. Meetings, Chicago, IL*.
- Holtan, H. N. 1961. A concept for infiltration estimates in watershed engineering. *Agri. Res. Ser. 41-51, U.S.G.P.O., Washington, DC*. 25 pp.
- Holtan, H. N. and N. R. Creitz. 1967. Influence of soils, vegetation and geomorphology on elements of the flood hydrograph, pp. 755-767. *Proc. Symposium Floods and Their Computation. Pub. 85, Vol. II, Part III. Inter. Assoc. of Sci. Hydrol., Leningrad, U.S.S.R.*
- Holtan, H. N. and M. H. Kirkpatrick, Jr. 1950. Rainfall, infiltration, and hydraulics of flow in runoff computation. *Trans. Amer. Geophysical Union* 31(5):771-779 .
- Holtan, H. N. and N. E. Minshall. 1968. Plot samples of watershed hydrology. *Agri. Res. Ser. 41-133, U.S.G.P.O., Washington, DC*. 206 pp.
- Horner, W. W. and C. L. Lloyd. 1940. Infiltration-capacity values as determined from a study of an eighteen-month record at Edwardsville, Illinois. *Trans. Amer. Geophysical Union* 21(Part II):522-541.
- Horton, R. E. 1933. The role of infiltration in the hydrologic cycle. *Trans. Amer. Geophysical Union* 14:446-460.
- Horton, R. E. 1937a. Determination of infiltration-capacity for large drainage basins. *Trans. Amer. Geophysical Union* 37(Part II):371-385.
- Horton, R. E. 1937b. Hydrologic interrelations of water and soils. *Soil Sci. Soc. Amer. Proc.* 1:401-429.

- Horton, R. E. 1940. An approach toward a physical interpretation of infiltration-capacity. *Soil Sci. Soc. Amer. Proc.* 5:399-417.
- Horton, R. E. 1945. Erosional development of streams and their drainage basins; hydrophysical approach to quantitative morphology. *Geol. Soc. Amer. Bull.* 56(3):275-370.
- Huff, F. A. and S. A. Changnon, Jr. 1972. Climatological assessment of urban effects on precipitation at St. Louis. *Journ. Applied Meteor.* 11(5):823-842.
- Hursh, C. R. 1944. Water storage limitations in forest soil profiles. *Soil Sci. Soc. Amer. Proc.* 8:412-414.
- Hursh, C. R. and M. D. Hoover. 1942. Soil profile characteristics pertinent to hydrologic studies in the southern Appalachians. *Soil Sci. Soc. Amer. Proc.* 6:414-422.
- Jackson, M. L. 1974. *Soil Chemical Analysis: Advanced Course*. 2nd Ed. Published by the author, Dept. of Soil Science, Univ. of Wisconsin, Madison. 875 pp.
- Johnson, A. I. 1963. A field method for measurement of infiltration. U.S. Geological Survey Water-Supply Paper 1544-F, U.S.G.P.O., Washington, DC. 27 pp.
- Johnson, W. M., J. E. McClelland, S. B. McCaleb, R. Ulrich, W. G. Harper and T. B. Hutchings. 1960. Classification and description of soil pores. *Soil Sci.* 89(5):319-321.
- Kelling, K. A. and A. E. Peterson. 1975. Urban lawn infiltration rates and fertilizer runoff losses under simulated rainfall. *Soil Sci. Soc. Amer. Proc.* 39(2):348-352.
- Khalifa, E. M. and S. W. Buol. 1968. Studies of clay skins in a Cecil (Typic Hapludult) soil: I. Composition and genesis. *Soil Sci. Soc. Amer. Proc.* 32(6):857-861.
- Khalifa, E. M. and S. W. Buol. 1969. Studies of clay skins in a Cecil (Typic Hapludult) soil: II. Effect on plant growth and nutrient uptake. *Soil Sci. Soc. Amer. Proc.* 33(1):102-105.
- Kirkby, M. J. and R. J. Chorley. 1967. Throughflow, overland flow and erosion. *Internat. Assoc. Sci. Hydrol. Bull.* 12(3):5-21.
- Klute, A. 1965. Laboratory measurement of hydraulic conductivity of saturated soil, pp. 210-221. *In* C. A. Black (ed.), *Methods of Soil Analysis*. Part 1. Physical and Mineralogical Properties, Including Statistics of Measurement and Sampling. Amer. Soc. Agron., Inc., Madison, WI.
- Klute, A. 1972. The determination of the hydraulic conductivity and diffusivity of unsaturated soils. *Soil Sci.* 113(4):264-276.

- Klute, A. 1973. Soil water flow theory and its application in field situations, pp. 9-35. In R. R. Bruce (ed.), Field Soil Water Regime. Special Public. Series No. 5. Soil Sci. Soc. Amer., Inc., Madison, WI.
- Learner, R. W. and J. F. Lutz. 1940. Determination of pore-size distribution of soils. Soil Sci. 49:347-360.
- Leopold, L. B. 1968. Hydrology for urban land planning—A guidebook on the hydrologic effects of urban land use. U.S. Geological Survey Circ. 554, U.S. Geological Survey, Washington, DC. 18 pp.
- Ligon, J. T. and T. V. Wilson. 1972. Deep seepage on Piedmont watersheds. Report No. 29, Water Resour. Res. Institut., Clemson Univ., Clemson, SC.
- Lutz, J. F. 1934. The structure of soils as affecting soil erosion. Amer. Soil Sur. Assoc. Bull. 15:98-100.
- Lutz, J. F. 1970. Movement and storage of water in North Carolina soils. Soil Information Series No. 15, Dept. of Soil Science, N. C. State Univ., Raleigh. 29 pp.
- Marotz, G. A. and J. C. Coiner. 1973. Acquisition and characterization of surface material data for urban climatological studies. Journ. Applied Meteor. 12(6):919-923.
- Marshall, T. J. 1958. A relation between permeability and size distribution of pores. Journ. Soil Sci. 9(1):1-8.
- Martens, L. A. 1968. Flood inundation and effects of urbanization in metropolitan Charlotte, North Carolina. Water-Supply Paper 1591-C, U.S. Geological Survey, Washington, DC. 60 pp. (Maps).
- Matzdorf, K. D., D. K. Cassel, B. K. Worcester and D. D. Malo. 1975. In situ hydraulic conductivity at four hillslope locations in a closed drainage system. Soil Sci. Soc. Amer. Proc. 39(3): 508-512.
- McCracken, R. J., E. J. Pedersen, L. E. Aull, C. I. Rich and T. C. Peele. 1971. Soils of the Hayesville, Cecil and Pacolet series in the southern Appalachian and Piedmont regions of the United States. Southern Cooperative Series Bull. No. 157, N. C. State University, Raleigh. 60 pp.
- McPherson, M. B. 1974. Urban runoff, pp. 154-176. Hydrological Effects of Urbanization. United Nations Educational, Scientific and Cultural Organization, Paris, France.

- McPherson, M. B. 1975. Regional earth science information in local water management. Urban Water Resour. Res. Council, Amer. Soc. Civil Engin., New York. 153 pp.
- Miller, C. R. and W. Viessman, Jr. 1972. Runoff volumes from small urban watersheds. Water Resour. Res. 8(2):429-434.
- Minshall, N. E. and V. C. Jamison. 1965. Interflow in claypan soils. Water Resour. Res. 1(3):381-390.
- Murphy, C. P., P. Bullock and K. J. Biswell. 1977a. The measurement and characterisation of voids in soil thin section by image analysis. Part II. Applications. Soil Sci. 28(3):509-518.
- Murphy, C. P., P. Bullock and R. H. Turner. 1977b. The measurement and characterisation of voids in soil thin sections by image analysis. Part I. Principles and techniques. Soil Sci. 28(3): 498-508.
- Musgrave, G. W. 1955. How much of the rain enters the soil? pp. 151-159. USDA Yearbook of Agriculture. U.S. Department of Agriculture, U.S.G.P.O., Washington, DC.
- Musgrave, G. W. and G. R. Free. 1936. Some factors which modify the rate and total amount of infiltration of field soils. Amer. Soc. Agron. Journ. 28(9):727-739.
- Musgrave, G. W. and H. N. Holtan. 1964. Infiltration, pp. 12.1-12.30. In V. T. Chow (ed.), Handbook of Applied Hydrology, A Compendium of Water-Resources Technology. McGraw-Hill, Inc., New York.
- Myers, V. A. 1969. The estimation of extreme precipitation as the basis for design floods—Resume of practice in the United States, pp. 84-101. Proceedings of Leningrad Symposium on Floods and Their Computation. International Assoc. Sci. Hydrol., U.N.E.S.C.O., Paris, France.
- Nelson, W. R. and L. D. Baver. 1940. Movement of water through soils in relation to the nature of the pores. Soil Sci. Soc. Amer. Proc. 5:69-76.
- Nielsen, D. R., J. W. Biggar and K. T. Erh. 1973. Spatial variability of field-measured soil-water properties. Hilgardia 42(7):215-260.
- Nielsen, D. R., J. M. Davidson, J. W. Biggar and R. J. Miller. 1964. Water movement through Panoche clay loam soil. Hilgardia 35(17): 491-506.
- Nielsen, D. R., R. D. Jackson, J. W. Gary and D. D. Evans (eds.). 1972. Soil Water. Amer. Soc. Agron. and Soil Sci. Soc. Amer., Madison, WI. 175 pp.

- Nutter, W. L. 1973. The role of soil water in hydrologic behavior of upland basins, pp. 181-193. In R. R. Bruce, K. W. Flach and H. M. Taylor (eds.), Field Soil Water Regime. Spec. Publ. No. 5. Soil Sci. Soc. Amer., Inc., Madison, WI.
- Parry, M. 1956. An "urban rainstorm" in the Reading area. Weather 11:41-48.
- Parsons, D. A. 1939. Operation of the type-F artificial rainfall apparatus. Research In-Service Report, Soil Conservation Service, U.S. Dept. of Agriculture, U.S.G.P.O., Washington, DC.
- Phillip, J. R. 1969. Theory of infiltration. Adv. Hydrosoci. 5:215-296.
- Putnam, A. L. 1972. Effect of urban development on floods in the Piedmont province of North Carolina. Open-File Report, U.S. Geological Survey, Raleigh, NC. 87 pp.
- Qashu, H. K. and S. W. Buol. 1967. Hydraulic and micromorphological properties of stream channel sediments. Water Resour. Res. 3(2): 465-469.
- Rogaar, H. 1974. Polyester casts for the study of the pore structure in soils. Neth. Journ. Agri. Sci. 22:143-152.
- Schiff, L. and F. R. Dreibelbis. 1949. Infiltration, soil moisture, and land use relationships with reference to surface runoff. Trans. Amer. Geophysical Union 30(1):75-88.
- Schneider, W. J. and J. E. Goddard. 1974. Extent and development of urban flood plains. Circular 601-J, U.S. Geological Survey, Washington, DC. 14 pp.
- Shanks, R. W. and A. R. Rao. 1977. The effects of urbanization on low flows and total runoff: Systematic development of methodologies in planning urban water resources for medium size communities. Tech. Rep. No. 94, Water Resour. Res. Inst., Purdue University, Lafayette, IN. 101 pp.
- Sharp, A. L. and H. N. Holtan. 1940. A graphical method of analysis of sprinkled-plot hydrographs. Trans. Amer. Geophysical Union 21 (Part II):558-570.
- Sharp, A. L. and H. N. Holtan. 1942. Extension of graphic methods of analysis of sprinkled-plot hydrographs to the analysis of hydrographs of control-plots and small homogeneous watersheds. Trans. Amer. Geophysical Union 23(Part II):578-593.
- Sharp, A. L., H. N. Holtan and G. W. Musgrave. 1949. Infiltration in relation to runoff on small watersheds. Tech. Publ. No. 81, Soil Conservation Service, U.S. Dept. of Agriculture, U.S.G.P.O., Washington, DC.

- Sherman, L. K. 1940. Derivation of infiltration-capacity (f) from average loss-rates (f_{av}). Trans. Amer. Geophys. Union 21:541-550.
- Snyder, F. F. 1958. Synthetic flood frequency. Proc. Amer. Soc. Civil Engin., Jour. Hydraulic Div. 84(5):1008.1-1008.22.
- Snyder, F. F. 1970. Discussion of paper—Urban runoff by road research laboratory method. Proc. Amer. Soc. Civil Engin., Jour. Hydraulic Div. 96(7):1626-1629.
- Soil Conservation Service. 1954. Hydrology Guide for Use in Watershed Planning. U.S. Dept. of Agriculture, U.S.G.P.O., Washington, DC.
- Soil Conservation Service. 1972. SCS National Engineering Handbook Section 4—Hydrology. U.S. Dept. of Agriculture, U.S.G.P.O., Washington, DC. 667 pp.
- Soil Conservation Service. 1975. Urban Hydrology for Small Watersheds. U.S. Dept. of Agriculture, U.S.G.P.O., Washington, DC. 98 pp.
- Soil Survey Investigations. 1972. Soil survey laboratory methods and procedures for collecting soil samples. Report No. 1, Soil Conservation Service, U.S. Dept. of Agriculture, U.S.G.P.O., Washington, DC. 503 pp.
- Soil Survey Staff. 1951. Soil Survey Manual. Agriculture Handbook No. 18, Soil Conservation Service, U.S. Dept. of Agriculture, U.S.G.P.O., Washington, DC.
- Soil Survey Staff. 1975. Soil Taxonomy: A Basic System of Soil Classification for Making and Interpreting Soil Surveys. Agricultural Handbook No. 436, Soil Conservation Service, U.S. Dept. of Agriculture, U.S.G.P.O., Washington, DC. 754 pp.
- Stewart, J. E. (ed.). 1978. Proceedings North Carolina workshop on management of stormwater, sedimentation and flood control in urban areas. Water Resour. Res. Instit., Univ. of North Carolina, Raleigh. 55 pp.
- Swartzendruber, D. and T. C. Olson. 1961. Model study of the double-ring infiltrometer as affected by depth of wetting and particle size. Soil Sci. 92(4):219-225.
- Tischendorf, W. G. A. 1969. Tracing stormflow to varying source areas in a small forested watershed in the southeastern Piedmont. Unpublished Ph.D. thesis, Dept. Hydrology, Univ. Georgia, Athens. Univ. Microfilms Int., Ann Arbor, MI.
- Tucker, L. S. 1969. Sewered drainage catchments in major cities. Tech. Memo No. 10, Urban Water Resources Research Program, Amer. Soc. Civil Engin., New York.

- U.S. Department of Commerce. 1973. 1970 Census of Population. Bureau of Census, Vol. 1, Part 35. U.S.G.P.O., Washington, DC. 1090 pp.
- U.S. Weather Bureau. 1955. Rainfall intensity-duration-frequency curves for selected stations in United States, Alaska, Hawaiian Islands, and Puerto Rico. Tech. Paper 25, U.S.G.P.O., Washington, DC. 53 pp.
- Van der Plas, L. and S. Slager. 1964. A method to study the distribution of biopores in soils, pp. 411-419. In A. Jongerius (ed.), Soil Microscopy. Proc. 2nd Internat. Working Meeting on Soil Micromorphology. Elsevier Publ. Co., Inc., Amsterdam, Netherlands.
- Viessman, W., Jr. 1966. The hydrology of small impervious areas. Water Resour. Res. 2(3):405-412.
- Viessman, W., Jr. 1968. Runoff estimation for very small drainage areas. Water Resour. Res. 4(1):87-93.